


**WIRELESS ROUTER TENDA TX2L PRO AX1500/2.4:300MBPS&5GHZ:1201MBPSI/3XGLAN/1XGBWAN MU-MIMO**

Naziv: WIRELESS ROUTER TENDA TX2L PRO  
AX1500/2.4:300MBPS&5GHZ:1201MBPSI/3XGLAN/1XGBWAN  
MU-MIMO



Šifra: #BM346901735790581067

Barkod: 6932849424201

Proizvođač: TENDA

**Detalji**

Kategorija: RUTERI

Oznake:

Atributi:

**Cena**

Cena sa PDV: 7,490.00 RSD \*WEB CENA  
8,239.00 RSD \*Cena za odloženo web plaćanje

**Ostalo**

Opis:

<b>Wi-Fi standardi</b>	IEEE 802.11ax/ac/a/n 5GHz, IEEE 802.11ax/b/g/n 2.4GHz, Beamforming, MU-MIMO
<b>Ostali standardi</b>	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
<b>Ujedinjenje Wi-Fi mreža</b>	Da, moguće je ujediniti 2,4 GHz i 5 GHz u jednu Wi-Fi mrežu
<b>Frekvencija i EIRP</b>	2.4G: 2412-2472MHz (CH1-CH13), 5G: 5180-5240MHz (CH36-CH64), <20 dBm (2.4 GHz), <23 dBm (5 GHz)
<b>Sigurnost Wi-Fi</b>	WPA3-SAE, WPA-PSK, WPA2-PSK, WPA/WPA2-PSK, WPS (Wi-Fi Protected Setup)
<b>Bežični režimi</b>	Wireless Router, AP mode, Universal Repeater (Client+AP, WISP)
<b>Brzina prenosa</b>	5GHz: do 1201Mb/s, 2.4GHz: do 300Mb/s
<b>Interfejs</b>	1x Gigabit WAN (10/100/1000 Mb/s), 3x Gigabit LAN (10/100/1000), 1x

	dugme WPS/Reset
<b>DHCP</b>	DHCP Server, DHCP Client List, DHCP Static IP Address Reservation and Assignment
<b>Povezivanje na Internet</b>	Dynamic IP, Static IP, PPPoE, Unifi, Maxis, Maxis-special, Celcom, Digi, Manual
<b>Virtuelni server</b>	Port Forwarding, DMZ Host, UPnP
<b>Sigurnost</b>	Filtrovane klijenata, roditeljska kontrola
<b>DDNS</b>	No-ip, 88ip, Oray.com, DynDNS
<b>VPN</b>	IPSec Transparent Transmission, PPTP Transparent Transmission, L2TP Transparent Transmission, PPTP VPN Server, PPTP VPN Client, L2TP VPN Client
<b>Način upravljanja</b>	HTTP, Daljinsko web upravljanje, SMART aplikacija za mobilni telefon
<b>Specijalne funkcije</b>	Wi-Fi+ Mesh, Smart Traffic Prioritisation, Smart Wi-Fi Schedule, Smart LED On/Off, Tenda Cloud
<b>Firewall</b>	ICMP Flood Attack Defense, TCP Flood Attack Defense, UDP Flood Attack Defense, Ignore Ping Packet From WAN Port
<b>Firewall i ostalo</b>	IPv6, IPTV, Mreža za goste, VLAN, Kontrola propusnog opsega, MAC Clone, Static Routing, System Log, Network Time, Backup/Restore Settings, online ažuriranja firmvera
<b>LED indikacija</b>	1x Sys
<b>Antena</b>	5x 6 dBi
<b>Provedba</b>	indoor, desktop
<b>Napajanje</b>	12 V DC, 1A
<b>Hlađenje</b>	Pasivno
<b>Radna temperatura</b>	0° do 40 °C
<b>Dimenzije (v x š x d)</b>	244