

TENDA O9 OUTDOOR LONG RANGE POINT TO POINT CPE 5GHZ 11AC 867MBPS, 1XGBIT, 23DBI, 25KM

Naziv: TENDA O9 OUTDOOR LONG RANGE POINT TO POINT
CPE 5GHZ 11AC 867MBPS, 1XGBIT, 23DBI, 25KM

Slika:



Šifra: #BM346901739874856324

Barkod: 6932849429886

Proizvođač: TENDA

Detalji

Kategorija: RUTERI

Oznake: [Proveri dostupnost](#)

Atributi:

Cena

Cena sa PDV: 10,936.55 RSD *WEB CENA
12,030.21 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:

O9 5GHz 11ac 23dBi gigabit outdoor CPE is designed to PtP and PtMP solutions for privated ISP wireless connectivity, CCTV surveillance and data transmission. It features with 23dBi directional dual polarization antenna to provide an efficient way to pick up and maintain a stable long-distance connectivity up to 25km. Adopt of auto-bridging technology, two CPE can connect to each other automatically to make it easy to setup.

Main Features

- 5GHz 11ac 867Mbps
- One Gigabit ethernet port
- 23dbi dual polarization antenna
- IP65 weatherproof enclosure
- 6000V Lightning Protection
- AP,Station,WISP operating mode supported
- Up to 60 meters of flexible deployment with included PoE adapter

O9 5GHz 11ac 23dBi gigabit outdoor CPE is designed to PtP and PtMP solutions for privated ISP wireless connectivity, CCTV surveillance and data transmission. It features with 23dBi directional dual polarization antenna to provide an efficient way to pick up and maintain a stable long-distance connectivity up to 25km. Adopt of auto-bridging technology, two CPE can connect to each other automatically to make it easy to setup.

Dimension 391.5*280*223mm

Deployment Pole Mount

Application Scenarios PtP and PtMP wireless connection for Privated ISP access or CCTV Surveillance

Frequency Range 5GHz

Compliant Standards IEEE 802.11a/n/ac

Private TDMA Protocol TD-MAX

Maximum Wireless Rate 867Mbps

Interface 1*10/100/1000Mbps Ethernet Port

Antenna gain 23dBi

Antenna Beamwidth Horizontal: 10° Vertical: 10°

Reset Button 1

Power Consumption 7.5W

Waterproof Level IP65

LED indicator PoE/LAN,LED1,LED2,LED3

Power Method 24V0.5A

Passive PoE Lightning Protection 6000V

Passive power over ethenet via PoE/LAN (+4,5pins-7,8pins) Voltage range: 21-25V DC

Reception Sensitivity 11a 6Mbps -96dBm±1.5dBm 11n MCS7 HT20 -72dBm±1.5dBm 11ac MCS9 HT80 -65dBm±1.5dBm

Operating Mode AP/Station/WISP/P2MP/WDS Repeater/Router

Enable/Disable Wireless Radio Support SSID Hidden Support Wireless Client isolation Support SSID Isolation Support Channel Bandwidth 20/40/80MHz

Channel Shift Support Wireless Access Control Support Weak Signal Client Limitation Support Transmit Power Adjustable power by 1dBm

WMM Capable Support APSD Capable Support Wireless Security 64/128 WEP,WPA-PSK,WPA2-PSK,WPA&WPA2-PSK,WPA,WPA2

Transparent Bridge Support VLAN Tagging for SSID Support DHCP Server Support VPN Pass-through PPTP,L2TP

Remote Web access Support Schedule Reboot Support Page Timeout Support Ping Watchdog Support Dynamic DN Snoip, dyndns.org

Network Diagnoses Ping, Traceroute, Signal Scan

Time&Date Setting Support Firmware Upgrade Support Backup/Restore Configuration Support Username Management Support Syslog Support Managed By Controller PC Software -- CPE Assistant

Package Content 1*5GHz 11ac 23dBi Gigabit Outdoor CPE O9 1*PoE Power Adapter 1*Quick Installation Guide

Operation Temperature -30? ~ 60? **Storage Temperature** -40? ~ 70? **Operating Humidity** 10%~90% non-condensing **Storage Humidity** 10%~90% non-condensing

Default IP 192.168.2.1 **Default Login Username** admin **Default Login Password** admin **Certification** FCC/CE/RoHS