

LAN ROUTER TP-LINK TL-MR100 3G/4G LTE WIFI 5 DUALBAND 1XLAN/1XWAN 150MB/S

Naziv: LAN ROUTER TP-LINK TL-MR100 3G/4G LTE WIFI 5 DUALBAND 1XLAN/1XWAN 150MB/S

Slika:



Šifra: #BM4366901732377706824

Barkod: 6935364088804

Proizvođač: TP-LINK

Detalji

Kategorija: RUTERI

Oznake:

Atributi:

CenaCena sa PDV: 10,290.00 RSD *WEB CENA
11,319.00 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

HARDWARE FEATURES

| | |
|----------------------------------|---|
| Interface | 1 10/100Mbps LAN Port, 1 10/100Mbps LAN/WAN Port, 1 Micro SIM Card Slot |
| Button | WPS/Reset Button |
| External Power Supply(EU) | 9V/0.85A |
| Dimensions (W x D x H) | 6.06×4.49×1.42 in (154×114×36 mm) |
| Antenna | 2 Detachable External 4G LTE Antennas |
| Antenna Type | V3/APAC: 2 Internal 4G LTE Antennas V4/V2/V1: 2 Detachable 4G LTE Antennas |

WIRELESS FEATURES

| | |
|---------------------------|------------------|
| Wireless Standards | IEEE 802.11b/g/n |
| Frequency | 2.4 GHz |

| | |
|------------------------------|---|
| Signal Rate | 300 Mbps |
| Reception Sensitivity | 11g 54M: -74 dBm 11n HT20: -71 dBm 11n HT40: -68 dBm |
| Transmit Power | < 20 dBm (2.4 GHz) |
| Wireless Functions | Enable/Disable Wireless Radio, Wireless Schedule, WMM, Wireless Statistics |
| WAN Failover | Yes |
| Wireless Security | 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions |
| Network Type | 4G: FDD-LTE: B1/B3/B5/B7/B8/B20 (2100/1800/850/2600/900/800 MHz) TDD-LTE: B38/B40/B41 (2600/2300/2500 MHz) 3G: HSPA/UMTS: B1/B5/B8 (2100/850/900 MHz) |

SOFTWARE FEATURES

| | |
|------------------------|---|
| Security | IPv4 SPI Firewall, IP and MAC Address Binding |
| Operating Modes | 3G/4G Router, Wireless Router |
| WAN Type | Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access) |
| Management | Local Management, Remote Management |
| DHCP | Server, DHCP Client List, Address Reservation |
| Port Forwarding | ALG, Virtual Server, Port Triggering, UPnP, DMZ |
| Dynamic DNS | DynDns, NO-IP |
| Protocols | IPv4, IPv6 |
| Guest Network | 2.4 GHz Guest Network |
| Administration | Upgrade Firmware, Factory Default, System Log, Diagnostic Tools |

OTHERS

| | |
|-------------------------|---|
| Certification | CE, RoHS |
| Package Contents | 300 Mbps Wireless N 4G LTE TL-MR100 Power Adapter RJ45 Ethernet Cable Quick Installation Guide |
| Requirements | Microsoft Windows 98SE/NT/2000/XP/Vista™/7/8/8.1/10, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser Micro SIM Card |

Environment

Operating Temperature: 0°C~40°C
(32°F ~104°F)
Storage Temperature: -40°C~70°C
(-40°F ~158°F)
Operating Humidity: 10%~90% non-
condensing
Storage Humidity: 5%~90% non-
condensing

Link [LAN Router TP-LINK TL-MR100 3G/4G LTE WiFi
1xLAN/1xWAN 150mb/s](#)