

MATIČNA PLOČA 1851 GIGABYTE Z890 AORUS ELITE WIFI7 ICENaziv: MATIČNA PLOČA 1851 GIGABYTE Z890 AORUS ELITE
WIFI7 ICE

Slika:



Šifra: #BM811801733198520284

Barkod: 4719331865269

Proizvođač: GIGABYTE

Detalji

Kategorija: MATIČNE PLOČE

Oznake:

[Proveri dostupnost](#)

Atributi:

PROCESORSKO LEŽIŠTE: LGA 1851
CHIPSET: Z890
M.2: DA
PODRŽANA MEMORIJA: DDR5**Cena**

Cena sa PDV:

34,990.00 RSD *WEB CENA

38,489.00 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:

Model	Gigabyte Z890M AORUS ELITE WIFI7 ICE DDR5 Micro ATX LGA1851 Matična ploča
Procesorsko podnožje (Socket)	Intel Socket 1851
Skup čipova (Chipset)	Intel Z890M
Podrška za procesore	Support for Intel Core Ultra Processors L3 cache varies with CPU
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	4x 288-Pin DDR5
	Support for DDR5 9200(O.C) /

Podrška za memorije

9066(O.C) / 8933(O.C) / 8800(O.C) / 8600(O.C) / 8400(O.C) / 8266(O.C) / 8200(O.C) / 8000(O.C) / 7950(O.C) / 7900(O.C) / 7800(O.C) / 7600(O.C.) / 7400(O.C.) / 7200(O.C.) / 7000(O.C.) / 6800(O.C.) / 6600(O.C.) / 6400 / 6200 / 6000 / 5800 / 5600MT/s memory modules.
Support for DDR5 6400/5600 MT/s memory modules
4 x DDR5 DIMM sockets supporting up to 256 GB (64 GB single DIMM capacity) of system memory
Dual channel memory architecture
Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)
Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules
Support for Extreme Memory Profile (XMP) memory modules
Support CUDIMM memory module

Podrška za grafiku - portovi

Integrated Graphics Processor-Intel HD Graphics support:
- 1 x USB4 USB Type-C port, supporting USB4 and DisplayPort video outputs and a maximum resolution of 3840x2160 144Hz
Support for DisplayPort 2.1 version

- 1 x DisplayPort, supporting a maximum resolution of 3840x2160 144Hz
Support for DisplayPort 2.1 version

- 1 x front HDMI port, supporting a maximum resolution of 1920x1080 30Hz
Support for HDMI 1.4 version

Slotovi za proširenja

CPU:
- 1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16)
The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot.

Chipset:
- 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x4 (PCIEX4)

M.2 portovi

3x M.2 Socket 3

Čuvanje podataka - portovi

CPU:
- 1 x M.2 connector (Socket 3, M key, type 2580/2280 PCIe 5.0 x4/x2 SSD support) (M2A_CPU)
- 1 x M.2 connector (Socket 3, M key, type 2580/2280 PCIe 4.0 x4/x2 SSD support) (M2B_CPU)
Chipset:
- 1 x M.2 connector (Socket 3, M key, type 25110/22110/2580/2280 PCIe 4.0 x4/x2 SSD support) (M2Q_SB)
- 4 x SATA 6Gb/s connectors
RAID 0, RAID 1, RAID 5, and RAID 10 support for NVMe SSD storage devices
RAID 0, RAID 1, RAID 5, and RAID 10

	support for SATA storage devices
SATA portovi	4x SATA 6Gb/s
LAN	Realtek 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
Bežična mreža	MediaTek Wi-Fi 7 MT7925 (PCB rev. 1.0) - 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency bands - Support for 11be 160MHz wireless standard Realtek Wi-Fi 7 RTL8922AE (PCB rev. 1.1) - 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency bands - Support for 11be 160MHz wireless standard
Bluetooth	5.4
Zvuk (Audio)	Realtek Audio CODEC High Definition Audio 2/4/5.1/7.1-channel Support for S/PDIF Out
USB portovi	CPU: - 1 x USB4 USB Type-C port on the back panel Chipset: - 1 x USB Type-C port with USB 3.2 Gen 2 support, available through the internal USB header - 1 x USB 3.2 Gen 2 Type-A port (red) on the back panel - 6 x USB 3.2 Gen 1 ports (4 ports on the back panel, 2 ports available through the internal USB header) Chipset+2 USB 2.0 Hubs: - 8 x USB 2.0/1.1 ports (4 ports on the back panel, 4 ports available through the internal USB headers)
Konektori na zadnjoj strani	1 x USB4 USB Type-C port (DisplayPort(Note)) 1 x USB 3.2 Gen 2 Type-A port (red) 4 x USB 3.2 Gen 1 ports 4 x USB 2.0/1.1 ports 2 x antenna connectors (2T2R) 1 x DisplayPort (Note) 1 x RJ-45 port 1 x optical S/PDIF Out connector 2 x audio jacks Actual support may vary by CPU.
Unutrašnji	1 x 24-pin ATX main power connector 2 x 8-pin ATX 12V power connectors 1 x CPU fan header 1 x CPU fan/water cooling pump header 3 x system fan headers 1 x system fan/water cooling pump header 3 x addressable RGB Gen2 LED strip headers 1 x RGB LED strip header 3 x M.2 Socket 3 connectors 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header

konektori	1 x USB Type-C header, with USB 3.2 Gen 2 support 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 2 x Thunderbolt™ add-in card connectors 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only) 1 x HDMI port 1 x power button 1 x reset button 1 x Q-Flash Plus button 1 x reset jumper 1 x Clear CMOS jumper
Posebne mogućnosti	Voltage detection Temperature detection Fan speed detection Water cooling flow rate detection Fan fail warning Fan speed control Support for GIGABYTE Control Center (GCC) Support for Q-Flash Support for Q-Flash Plus Support for Smart Backup
Operativni sistem	Windows 11
BIOS	1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Format	Micro ATX
Prava potrošača:	Zakonska saobraznost 2 godine
EAN:	4719331865269