

**MB AM4 ASUS PRIME B450M-K II**

Naziv: MB AM4 ASUS PRIME B450M-K II

Slika:



Šifra: #BM7611801726042364667

Barkod: 4718017932387

Proizvođač: ASUS

**Detalji**

Kategorija: MATIČNE PLOČE

Oznake:

[Proveri dostupnost](#)

Atributi:

**Cena**Cena sa PDV: 10,029.00 RSD \*WEB CENA  
11,031.90 RSD \*Cena za odloženo web plaćanje**Ostalo**

Opis:

Podnožje	AMD® AM4
Čipset	AMD® B450
Tip procesora	AMD
Format ploče	Micro ATX
Podržani procesori	AMD AM4 Socket AMD Ryzen™ druge generacije/Ryzen™ sa Radeon™ Vega grafikom/Ryzen™ prve generacije.
Podržana memorija	DDR4
Memorija	2 x DIMM, maksimalni podržani kapacitet 32GB, DDR4 3200(O.C.)/3000(O.C.)/2933(O.C.)/2800(O.C.)/2666/2400/2133 MHz nebaferovane memorije. Dvokanalna arhitektura memorije. Podrška za ECC memoriju (ECC mod) varira u odnosu na mikroprocesor.
Integrirana grafička karta	AMD Ryzen™ sa Radeon™ Vega grafičkim procesorom Multi-VGA output podrška: DVI-D/D-Sub portovi - DVI-D, maksimalna rezolucija 1920 x 1200 @ 60 Hz - D-sub, maksimalna rezolucija 1920 x 1200 @ 60 Hz
Slotovi za	AMD Ryzen™ druge generacije/Ryzen™ prve generacije: 1 x PCIe 3.0/2.0 x16 (x16 mode) AMD Ryzen™ sa Radeon™ Vega

proširenje	grafikom: 1 x PCIe 3.0/2.0 x16 (x8 mode) *1 AMD B450 chipset: 2 x PCIe 2.0 x1
Skladište	AMD B450 chipset: 4 x SATA 6Gb/s port(s), gray, Support Raid 0, 1, 10 AMD Ryzen™ druge generacije/Ryzen™ sa Radeon™ Vega grafikom/Ryzen™ prve generacije: 1 x M.2 Socket 3, with M key, type 2242/2260/2280 storage devices support (SATA & PCIE 3.0 x 4 mode)
Mrežna karta	Realtek® RTL8111H, 1 x Gigabit LAN Controller(s) ASUS LAN Guard
Zvučna karta	Realtek® ALC887 8-Channel High Definition Audio CODEC
USB	AMD Ryzen™ druge generacije/Ryzen™ sa Radeon™ Vega grafikom/Ryzen™ prve generacije: 4 x USB 3.1 Gen 1 port(s) (4 na zadnjem panelu) AMD B450 chipset : 2 x USB 3.1 Gen 2 port(s) (2 na zadnjem panelu) AMD B450 chipset : 2 x USB 3.1 Gen 1 port(s) (2 na midboard-u) AMD B450 chipset : 4 x USB 2.0/1.1 port(s) (4 na midboard-u)
Konektori na zadnjoj strani	1 x PS/2 keyboard (purple) 1 x PS/2 mouse (green) 1 x DVI-D 1 x D-Sub 1 x LAN (RJ45) port(s) 2 x USB 3.1 Gen 2 4 x USB 3.1 Gen 1 , 3 x Audio jack(s)
Interni konektori	1 x USB 3.1 Gen 1(up to 5Gbps) connector(s) support(s) additional 2 USB 3.1 Gen 1 port(s) (19-pin) 2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s) 1 x M.2 Socket 3 with M key, type 2242/2260/2280 storage devices support (SATA & PCIE 3.0 x 4 mode) 1 x COM port(s) connector(s) 4 x SATA 6Gb/s connector(s) 1 x CPU Fan connector(s) (1 x 4 -pin) 1 x Chassis Fan connector(s) (1 x 4 -pin) 1 x S/PDIF out header(s) 1 x 24-pin EATX Power connector(s) 1 x 8-pin ATX 12V Power connector(s) 1 x Front panel audio connector(s) (AAFP) 1 x System panel(s) 1 x Clear CMOS jumper(s) 1 x Speaker connector
BIOS	128 Mb Flash ROM, UEFI AMI BIOS, PnP, SM BIOS 3.1, ACPI 6.1, višejezični BIOS, ASUS EZ Flash 3, ASUS CrashFree BIOS 3, F3 My Favorite, Last Modified log, F12 PrintScreen, ASUS DRAM SPD (Serial Presence Detect) memory information, F6 Qfan Control
Ostalo	ASUS 5X Protection III: - ASUS SafeSlot Core: Ograđen PCIe Slot sprečava oštećenja - ASUS LANGuard: Štiti od LAN upada, udara groma i pražnjenja statičkog elektriciteta! - ASUS Overvoltage Protection: Zaštita od prevelike voltaže - ASUS zadnji I/O panel od nerđajućeg čelika za veću izdržljivost - ASUS DIGI+ VRM: 6 Phase digital power design ASUS Exclusive Features: - AI Suite 3 - Ai Charger ASUS Quiet Thermal Solution : - Stylish Fanless Design Heat-sink solution - ASUS Fan Xpert ASUS EZ DIY : - ASUS CrashFree BIOS 3 - ASUS EZ Flash 3 - ASUS UEFI BIOS EZ Mode - Multi-language BIOS ASUS Q-Design : - ASUS Q-Slot - ASUS Q-DIMM