


MB S1700 ASUS PRIME H770-PLUS

Naziv:	MB S1700 ASUS PRIME H770-PLUS
Slika:	
Šifra:	#BM7611801726042490635
Barkod:	4711387258347
Proizvođač:	ASUS

Detalji

Kategorija:	MATIČNE PLOČE
Oznake:	
Atributi:	

Cena

Cena sa PDV:	26,195.00 RSD *WEB CENA 28,814.50 RSD *Cena za odloženo web plaćanje
--------------	---

Ostalo

Opis:	
Model	Asus PRIME H770-PLUS D4 LGA1700 ATX Matična ploča
Procesorsko podnožje (Socket)	Intel Socket 1700 (LGA1700)
Skup čipova (Chipset)	Intel® H770
Podrška za procesore	Intel® Socket LGA1700 for 13th Gen Intel® Core™ & 12th Gen Intel® Core™, Pentium® Gold and Celeron® Processors Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0
Tip memorije (RAM)	DDR4
Broj memorijskih slotova	4x 288-Pin DDR4
Podrška za memorije	4 x DIMM, Max. 128GB, DDR4 5066(OC)/5000(OC)/4800(OC)/4600(OC)/4400(OC)/4266(OC)/4000(OC)/3733(OC)/3600(OC)/3466(OC)/3400(OC)/3333(OC)/3200/3000/2933/2800/2666/2400/2133 Non-ECC, Un-buffered Memory Dual Channel Memory Architecture Supports Intel® Extreme Memory Profile (XMP) OptiMem
Podrška za grafiku - portovi	1 x DisplayPort 1 x HDMI® port Supports max. 4K@60Hz as specified in DisplayPort 1.4. Supports 4K@60Hz as specified in HDMI® 2.1.
Slotovi za proširenja	Intel® 13th & 12th Gen Processors 1 x PCIe 5.0 x16 slot Intel® H770 Chipset 2 x PCIe 4.0 x16 slots (support x4 mode) 2 x PCIe 3.0 x1 slots
M.2 portovi	3x M.2 Socket 3
Čuvanje podataka - portovi	Intel® 13th & 12th Gen Processors M.2_1 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode) Intel® H770 Chipset M.2_2 slot (Key M), type 2242/2260/2280/22110 (supports PCIe 4.0 x4 mode) M.2_3 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 & SATA modes) 4 x SATA 6Gb/s ports Intel® Rapid Storage Technology supports PCIe RAID 0/1/5/10, SATA RAID 0/1/5/10.
U.2 portovi	nema
SATA Express portovi	nema
SATA portovi	4x SATA 6Gb/s
LAN	1 x Realtek 2.5Gb Ethernet
Zvuk (Audio)	Realtek 7.1 Surround Sound High Definition Audio CODEC - Supports: Jack-detection, Multi-streaming, Front Panel Jack-retasking - Supports up to 24-Bit/192 kHz playback Audio Features - Audio Shielding - Premium audio capacitors - Dedicated audio PCB layers
USB portovi	Rear USB (Total 8 ports) 3 x USB 3.2 Gen 2 ports (2 x Type-A + 1 x USB Type-C®) 3 x USB 3.2 Gen 1 ports (3 x Type-A) 2 x USB 2.0 ports (2 x Type-A) Front USB (Total 7 ports) 2 x USB 3.2 Gen 1 headers support 4 additional USB 3.2 Gen 1 ports

	2 x USB 2.0 headers support 3 additional USB 2.0 ports
Konektori na zadnji strani	<ul style="list-style-type: none"> 3 x USB 3.2 Gen 2 ports (2 x Type-A + 1 x USB Type-C®) 3 x USB 3.2 Gen 1 ports (3 x Type-A) 2 x USB 2.0 ports (2 x Type-A) 1 x DisplayPort 1 x HDMI® port 1 x Vertical M.2 slot (Key E) 1 x Realtek 2.5Gb Ethernet port 3 x Audio jacks
Unutrašnji konektori	<ul style="list-style-type: none"> Fan and Cooling related 1 x 4-pin CPU Fan header 1 x 4-pin AIO Pump header 3 x 4-pin Chassis Fan headers Power related 1 x 24-pin Main Power connector 1 x 8-pin +12V Power connector Storage related 3 x M.2 slots (Key M) 4 x SATA 6Gb/s ports USB 2 x USB 3.2 Gen 1 headers support 4 additional USB 3.2 Gen 1 ports 2 x USB 2.0 headers support 3 additional USB 2.0 ports Miscellaneous 3 x Addressable Gen 2 headers 2 x Aura RGB headers 1 x Clear CMOS header 1 x COM Port header 1 x Front Panel Audio header (AAFP) 1 x S/PDIF Out header 1 x SPI TPM header (14-1pin) 1 x 20-3 pin System Panel header with Chassis intrude function 1 x Thunderbolt™ (USB4®) header
Posebne mogućnosti	<ul style="list-style-type: none"> ASUS 5X PROTECTION III - DIGI+ VRM - LANGuard - Overvoltage Protection - SafeSlot Core+ - Stainless-Steel Back I/O ASUS Q-Design - Q-DIMM - Q-LED Core - Q-Slot ASUS Thermal Solution - M.2 heatsink - VRM heatsink design ASUS EZ DIY - ProCool Aura Sync - Aura RGB headers - Addressable Gen 2 headers
Operativni sistem	Windows 10; Windows 11
BIOS	192 (128+64) Mb Flash ROM, UEFI AMI BIOS
Format	ATX