

MB AM5 ASUS PRIME B650M-A II-CSM

Naziv:

MB AM5 ASUS PRIME B650M-A II-CSM

Slika:



Šifra:

#BM7611801726045470656

Barkod:

4711387025543

Proizvođač:

ASUS

Detalji

Kategorija:

MATIČNE PLOČE

Oznake:

Atributi:

Cena

Cena sa PDV:

29,951.00 RSD *WEB CENA

32,946.10 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:

Procesorsko ležište (socket)	AMD AM5
Čipset	AMD B650
Grafika	Upotreba grafike iz procesora
Tip memorije	DDR5
Memorijski slotovi	4x DDR5
Podržane memorije	6.000MT/s (O.C.), 5.800MT/s (O.C.), 7.200MT/s (O.C.), 7.000MT/s (O.C.), 6.800MT/s (O.C.), 6.600MT/s (O.C.), 6.400MT/s (O.C.), 6.200MT/s (O.C.), 5.200MT/s, 5.000MT/s, 4.800MT/s, 5.600MT/s (O.C.), 5.400MT/s (O.C.), 7.600+MT/s (O.C.)
Maksimalna ukupna memorija	192GB
Ostale osobine	OptiMem II, Dual Channel, Podrška za AMD EXTended Profiles for Overclocking (EXPO)

PCI Express x16 slot	1x PCI Express 4.0 (x16 mode), 2x PCI Express 4.0 (x1 mode), 1x PCI Express 4.0 (x8/x4 mode)
SATA priključci (ukupno)	4
SATA priključci	4x SATA 6GB/s
Ostali skladišni interfejs	2 x M.2
RAID	RAID 0, RAID 1, RAID 10
Žična mreža (LAN)	1x Realtek 2.5Gb Ethernet
Model	Realtek
Broj kanala	7.1
Model	Realtek
Napomena	Audio Shielding, Jack-detection, Multi-streaming, Front Panel Jack-retasking, Premium audio capacitors, Dedicated audio PCB layers
DisplayPort priključci	1x DisplayPort
HDMI priključci	1
VGA D-sub	1
PS/2	1 (tastatura ili miš)
Ukupno USB priključaka	8
USB 3.2 priključci	2 (Tip A) Gen2, 2 (Tip A) Gen1
USB 2.0 priključci	4 (Tip A)
RJ-45 (LAN)	1
Audio	3x 3.5mm
Ostali priključci	BIOS Flashback taster
Naponski priključci	1x 8 pin 12V Power Connector, 1 x 24 pin Main Power connector
USB 3.2	1 (podrška za 2 USB 3.2 Gen 1 porta), 1 (podrška za USB-C port)
USB 2.0	2 (podrška za 4 USB 2.0 porta)
Audio	1x Front panel header
Ostali priključci	4 x SATA 6Gb/s, 1 x S/PDIF Out header, 1 x speaker header, 3 x 4-pin Chassis Fan headers, 1 x 4-pin CPU OPT Fan header, 1 x 10-1 pin System Panel header, 1 x 4-pin CPU Fan header, 1 x 14-1 pin SPI TPM header, 1 x Clear CMOS header, 2 x M.2 slot (Key M), 3 x Addressable Gen 2 headers, 1 x COM Port header,

	1 x AURA RGB header
Napomena	Za iskorišćavanje određenih internih konektora potrebni su dodatni bracket-i ili priključci na kućištu
Podržane tehnologije	AURA Creator, AURA Sync, DIGI+VRM, ASUS EZ Flash 3, LANGuard, Overvoltage Protection, Fan Xpert 2+, TurboV EVO, PC Cleaner
Format	microATX
Dimenzije	244mm x 244mm