

LAN MK TP-LINK ARCHER T2U AC600 WIRELESS 600MB/S DUAL BAND USBNaziv: LAN MK TP-LINK ARCHER T2U AC600 WIRELESS
600MB/S DUAL BAND USB

Slika:



Šifra: #BM4366881733544136847

Barkod: 6935364089917

Proizvođač: TP-LINK

Detalji

Kategorija: MREŽNE KARTICE

Oznake:

Atributi: INTERFEJS: USB

CenaCena sa PDV: 1,911.00 RSD *WEB CENA
2,102.10 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

HARDWARE FEATURES**Interface** USB 2.0**LED** Status**Dimensions (W x D x H)** 1.6×0.7×0.3 in.
(41×19.5×8.7mm)**Antenna Type** Omni Directional**WIRELESS FEATURES****Wireless Standards** IEEE 802.11ac, IEEE 802.11a,
IEEE 802.11n, IEEE 802.11g, IEEE
802.11b**Frequency** 5GHz
2.4GHz**Signal Rate** 5GHz
11ac: Up to 433Mbps(dynamic)
11n: Up to 150Mbps(dynamic)
11a: Up to 54Mbps(dynamic)
2.4GHz
11n: Up to 150Mbps(dynamic)
11g: Up to 54Mbps(dynamic)
11b: Up to 11Mbps(dynamic)

Reception Sensitivity	5GHz : 11a 6Mbps: -94dBm 11a 54Mbps: -78dBm 11n HT20 MCS0: -94dBm 11n HT20 MCS7: -77dBm 11n HT40 MCS0: -92dBm 11n HT40 MCS7: -74dBm 11ac VHT80 MCS0: -89dBm 11ac VHT80 MCS9: -64dBm 2.4GHz: 11b 1Mbps: -99dBm 11b 11Mbps: -91dBm 11g 6Mbps: -94dBm 11g 54Mbps: -77dBm 11n HT20 MCS0: -95dBm 11n HT20 MCS7: -76dBm 11n HT40 MCS0: -92dBm 11n HT40 MCS7: -73dBm
Transmit Power	<20dBm (EIRP)
Wireless Modes	Ad-Hoc / Infrastructure mode
Wireless Security	Support 64/128 bit WEP, WPA-PSK/WPA2-PSK, 802.1x
Modulation Technology	DBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM
OTHERS	
Certification	FCC, RoHS
Package Contents	Wireless Adapter Archer T2U Resource CD Quick Installation Guide
System Requirements	Windows & MacOS
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing