


**3DP-PETG1.75-01-NAT PETG FILAMENT ZA 3D STAMPAC 1.75MM, KOTUR 1KG NATURAL**

|             |   |
|-------------|---|
| Naziv:      | 3DP-PETG1.75-01-NAT PETG FILAMENT ZA 3D STAMPAC 1.75MM, KOTUR 1KG NATURAL         |
| Slika:      |  |
| Šifra:      | #BM7715521739874498359  |
| Barkod:     | 8716309090780   |
| Proizvođač: | GEMBIRD   |

**Detalji**

|             |                               |
|-------------|-------------------------------|
| Kategorija: | 3D ŠTAMPAČI                   |
| Oznake:     | NOVO<br><b>NEMA NA STANJU</b> |

Atributi:

**Cena**

|              |   |
|--------------|---|
| Cena sa PDV: | 2,355.68 RSD *WEB CENA<br>2,591.25 RSD *Cena za odloženo web plaćanje |
|--------------|---|

**Ostalo**

|       |  |
|-------|--|
| Opis: | JEDNOSTAVNO ZA UPOTREBU Polyethylene terephthalate (PETG) je amorfna termoplastika poliestra Savršena kombinacija jasnoće i snage. Lako za štampanje sa raznim 3D štampačima. Vlakno je vrlo visoke čvrstoće Otporan na udarce-PETG je manje krt od akrila, i alternativa za nižu cenu od polikarbonata. Otporan na hemikalije - nudi superiornu hemijsku otpornost u poređenju sa mnogim drugim materijalima. Ekološki jer se može 100% reciklirati Lako se štampa na bilo kojoj podlozi Material: PETG, 1.75 mm diameter Weight: 1 kg/spool (2.2 lbs) Density at 240°C: 1.27 g/cm <sup>3</sup> Melt Flow Index at g/10min, 200°C/ 5kg: 20 Melt Point: 220 - 260 °C Heat-Deflection-Temperature at 0.455 MPa: 60 - 80 °C Yield Strength at 5mm/min: 50 MPa Impact Strength: 8.7 KJ/m <sup>2</sup> Ensile Break: 120 % Diameter: 1.75 ± 0.05 mm Spool dimensions: 200 mm diameter x 67 mm height x 53 mm central hole Sistemski zahtevi: 3D štampač sa 1.75mm ekstruder temperature oko 240 °C, pogodno za PETG vlakna |
|-------|--|