

**TENDA O9 OUTDOOR LONG RANGE POINT TO POINT CPE 5GHZ 11AC 867MBPS, 1XGBIT, 23DBI, 25KM**

Naziv: TENDA O9 OUTDOOR LONG RANGE POINT TO POINT  
CPE 5GHZ 11AC 867MBPS, 1XGBIT, 23DBI, 25KM

Slika:



Šifra: #BM346901739874856324

Barkod: 6932849429886

Proizvođač: TENDA

**Detalji**

Kategorija: RUTERI

Oznake: NOVO

**NEMA NA STANJU**

Atributi:

**Cena**

Cena sa PDV: 10,936.55 RSD \*WEB CENA  
12,030.21 RSD \*Cena za odloženo web plaćanje

**Ostalo**

Opis:

O9 5GHz 11ac 23dBi gigabit outdoor CPE is designed to PtP and PtMP solutions for privated ISP wireless connectivity, CCTV surveillance and data transmission. It features with 23dBi directional dual polarization antenna to provide an efficient way to pick up and maintain a stable long-distance connectivity up to 25km. Adopt of auto-bridging technology, two CPE can connect to each other automatically to make it easy to setup.

**Main Features**

- 5GHz 11ac 867Mbps
- One Gigabit ethernet port
- 23dbi dual polarization antenna
- IP65 weatherproof enclosure
- 6000V Lightning Protection
- AP,Station,WISP operating mode supported
- Up to 60 meters of flexible deployment with included PoE adapter

O9 5GHz 11ac 23dBi gigabit outdoor CPE is designed to PtP and PtMP solutions for privated ISP wireless connectivity, CCTV surveillance and data transmission. It features with 23dBi directional dual polarization antenna to provide an efficient way to pick up and maintain a stable long-distance connectivity up to 25km. Adopt of auto-bridging technology, two CPE can connect to each other automatically to make it easy to setup.

**Dimension** 391.5\*280\*223mm

**Deployment Pole Mount**

**Application Scenarios** PtP and PtMP wireless connection for Privated ISP access or CCTV Surveillance

**Frequency Range** 5GHz

**Compliant Standards** IEEE 802.11a/n/ac

**Private TDMA Protocol** TD-MAX

**Maximum Wireless Rate** 867Mbps

**Interface** 1\*10/100/1000Mbps Ethernet Port

**Antenna gain** 23dBi

**Antenna Beamwidth** Horizontal: 10° Vertical: 10°

**Reset Button** 1

**Power Consumption** 7.5W

**Waterproof Level** IP65

**LED indicator** PoE/LAN,LED1,LED2,LED3

**Power Method** 24V0.5A

**Passive PoE** Lightning Protection 6000V

**Passive power over ethenet via PoE/LAN (+4,5pins-7,8pins )** Voltage range: 21-25V DC

**Reception Sensitivity** 11a 6Mbps -96dBm±1.5dBm 11n MCS7 HT20 -72dBm±1.5dBm 11ac MCS9 HT80 -65dBm±1.5dBm

**Operating Mode** AP/Station/WISP/P2MP/WDS Repeater/Router

**Enable/Disable Wireless Radio** Support SSID Hidden Support Wireless Client isolation Support SSID Isolation Support Channel Bandwidth 20/40/80MHz

**Channel Shift Support** Wireless Access Control Support Weak Signal Client Limitation Support Transmit Power Adjustable power by 1dBm

**WMM Capable Support** APSD Capable Support Wireless Security 64/128 WEP,WPA-PSK,WPA2-PSK,WPA&WPA2-PSK,WPA,WPA2

**Transparent Bridge Support** VLAN Tagging for SSID Support DHCP Server Support VPN Pass-through PPTP,L2TP

**Remote Web access Support** Schedule Reboot Support Page Timeout Support Ping Watchdog Support Dynamic DN Snoip, dyndns.org

**Network Diagnoses** Ping, Traceroute, Signal Scan

**Time&Date Setting Support** Firmware Upgrade Support Backup/Restore Configuration Support Username Management Support Syslog Support Managed By Controller PC Software -- CPE Assistant

**Package Content** 1\*5GHz 11ac 23dBi Gigabit Outdoor CPE O9 1\*PoE Power Adapter 1\*Quick Installation Guide

**Operation Temperature** -30? ~ 60? **Storage Temperature** -40? ~ 70? **Operating Humidity** 10%~90% non-condensing **Storage Humidity** 10%~90% non-condensing

**Default IP** 192.168.2.1 **Default Login Username** admin **Default Login Password** admin **Certification** FCC/CE/RoHS