

IP-COM G1024D LAN 24-PORT 10/100/1000M BASE-T ETHERNET PORTS (MDI/MDIX) DESK/RACK MOUNT(ALT=TEG1024D

Naziv: IP-COM G1024D LAN 24-PORT 10/100/1000M BASE-T ETHERNET PORTS (MDI/MDIX) DESK/RACK MOUNT(ALT=TEG1024D

Slika:



Šifra: #BM4076931739874958551

Barkod: 6932392831501

Proizvođač: IP-COM

Detalji

Kategorija: LAN RUTERI

Oznake: NOVO

NEMA NA STANJU

Atributi:

Cena

Cena sa PDV: 11,722.42 RSD *WEB CENA
12,894.66 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:

Compliant with IEEE802.3, IEEE802.3u, IEEE802.3X, IEEE802.3ab standards
24*10/100/1000 Mbps auto-negotiation RJ45 ports
Auto MDI/MDIX
8000 MAC address and MAC auto Learning & Auto Aging
IEEE 802.3x full duplex flow control, and backpressure half duplex flow control
48 Gbps switching fabric for non-blocking line-speed forwarding
LED indicators for indicating working status and troubleshooting
Built-in power supply system with 6 kV common mode and 4 kV differential mode lightning protection
24 ports with 6 kV common mode lightning protection
IP camera connection
Plug and play
IP-COM G1024D is a 24-port gigabit unmanaged desktop/rack switch designed for video surveillance, offices, work groups, and SMEs for easy, economical and high-speed internet purposes. Its full duplex transmission rate can reach up to 2000 Mbps, ensuring the timely transfer of large files as well as smooth streaming videos. The professional integrated lightning protection circuit, the built-in power supply module, and all the 24 ports could withstand 6 kV lightning surge, ensuring the switch to run stably. G1024D is your ideal choice for extension, or upgrade to high-speed and stable gigabit optical network.
Stable connection for 7*24
24*10/100/1000 Mbps auto-negotiation RJ45 ports, up to 2000 Mbps of full duplex transmission rate, line-speed forwarding by all ports, and large cache capacity ensure the timely transfer of large files and stable streaming video. Stay connected for 7*24.
Excellent lightning protection of ports
Professional integrated lightning protection circuit enables all the 24 ports to provide IV-class (6 kV in common mode) lightning protection, effectively decreasing the damage rate to the ports by lightning surge.
Professional lightning protection for power supply
The built-in power supply module is designed with enhanced lightning protection, which can withstand 6 kV lightning surge, 3 times higher than other ordinary switches, effectively protecting the switch from being damaged by adverse thunderstorm.
Innovative design
Full steel housing and plating through holes in three faces allow higher-efficient heat dissipation; fanless design ensures the noiselessness and dust free, harmoniously fitting into the offices; 13-inch size makes it mountable both on desktop and rack and plug and play function makes it easy for use.
Standard & Protocol IEEE 802.3
IEEE 802.3u
IEEE 802.3x
IEEE 802.3ab
Forwarding Speed
10Mbps : 14880pps
100Mbps : 148800pps
1000Mbps : 1488000pps
Transmission Media
10BASE-T: UTP category 3, 4, 5 cable
100BASE-TX/1000BASE-T: UTP category 5, 5e or above cable
Port
24*10/100/1000Mbps auto-negotiation RJ 45 ports (Auto MDI/MDIX)
LED Indication 24* Link/Act indicator, 1*power indicator
Dimensions
297mm×178mm×44mm
Switch Feature
Store-and-Forward
MAC auto Learning & Auto Aging
8K MAC
48Gbps Backpanel bandwidth
Lighting Proof lightning protection 6KV for power supply, 6KV for all ports
Power Input 100~240V AC, 50/60Hz
Operating Environment
Temperature: 0~45
Humidity: 10%~90% non-condensing
Storage Environment
Temperature: -40~70
Humidity: 5%~90% non-condensing
Tenda