

DAHUA MREZNI KABAL CAT6 DH-PFM920I-6UN-C BAKARNI 305M

Naziv: DAHUA MREZNI KABAL CAT6 DH-PFM920I-6UN-C BAKARNI 305M



Šifra: #BM2677061739881635036

Barkod: 6939554998560

Proizvođač: DAHUA

Detalji

Kategorija: KABLOVI

Oznake:

Atributi:

CenaCena sa PDV: 28,268.32 RSD *WEB CENA
31,095.15 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

-305 m (1000 ft)/karton UTP CAT6, napajanje preko Ethernet, kompatibilan sa jednim kablom-Bakarni provodnik oxygen-free visoke cistoce-Prilagodeni PVC spoljni omotac; CE CPR Eca sertifikovana klasa otpornosti na vatruConductorMaterial: Oxygen free copper (99.97% purity)Diameter: 0.53 mm ± 0.01 mmInsulationMaterial: HDPEMin. Average Thickness: 0.21 mmDiameter: 0.95 mm ± 0.1 mmColor (4 Pairs): Blue, white/blue; orange, white/orange; green, white/green; brown, white/brownSeparatorMaterial: PESpecification: Translucent 4.5 × 0.4 mmRip CordMaterial: PolyesterSpecification: 500DSheathMaterial: PVCMin. Average Thickness: 0.5 mmDiameter: 6.0 mm ± 0.3 mmColor: WhiteElectricalMax. DC Resistance of a Single Conductor: 8.70/100 mMin. Insulation Resistance: 5000MO·kmMax. DC Resistance Unbalance: 2% (pair intra), 4% (pairs inter)Dielectric Strength: No breakdown with 1KV DC for 1 minTransmissionCharacteristic Impedance: 100 ± 15ONear End Cross Talk: =39.30 dB/100 m@250 MHzMax. Attenuation: 34.8 dB/100 m@250 MHzReturn Loss: =17.3 dB/100 m@250 MHzMechanicalTensile Strength: Sheath=13.5 MPa, insulation=16 MPaElongation at Break: Sheath=150%, insulation=300%Installation Bending Radius: >8 times of outer cable diameterConductor Elongation at Break: =10%EnvironmentalShrinkage of Insulation: =5%Color Migration Resistance of Insulation: No migrationSheath Tensile Strength and Elongation at Break after Aging: =12.5 MPa, =100%Low Temperature Bending Test: No cracking after the testHeat Shock Test: No cracking after the testOperating Temperature: -20°C to +60°C (-4°F to 140°F)Installation Temperature: 0°C to +50°C (32°F to 122°F)Storage Temperature and Humidity: -10°C to +40°C (14°F to 104°F), <60% (RH)SecurityVertical Fire Propagation Test: Comply with IEC 60332-1-2PackagingCable Length: 305.0 m (1000.66 ft) ± 1.5 m (4.92 ft)Inner Carton Dimensions: 416.0 mm × 412.0 mm × 220.0 mm (16.38" × 16.22" × 8.66") (L × W × H)Packaging Method: 305.0 m (1000.66 ft) a carton, one master carton with 2 inner cartonsNet Weight: =10.5 kg (23.15 lb)Gross Weight: =11.5 kg (25.35 lb)ComplianceExecutive Standards: Q/DXJ 067-2019, EN50575-2014Certification: CPR Eca