

MB AM5 ASROCK B850 PRO-A

Naziv: MB AM5 ASROCK B850 PRO-A

Slika:



Šifra: #BM42411801741665889928

Barkod: 4711581490185

Proizvođač: NEDEFINISAN

Detalji

Kategorija: MATIČNE PLOČE

Oznake: NOVO

Atributi: PROCESORSKO LEŽIŠTE (SOCKET): AMD® AM5
UKUPNO USB PRIKLJUČAKA: 8
TIP MEMORIJE: DDR5
MEMORIJSKI SLOTOVI: 4 X DDR5
MAKSIMALNA KOLIČINA MEMORIJE: 256
FORMAT: ATX**Cena**Cena sa PDV: 26,933.00 RSD *WEB CENA
29,626.30 RSD *Cena za odloženo web plaćanje**Ostalo**

- Opis:
- Unique Feature
Superb Productivity
 - PCIe Gen5 (Graphics, M.2)
 - Dual Channel DDR5
 - **Rock-Solid Durability**
 - 14+2+1 Power Phase, 80A Dr.MOS for VCore+SOC+MISC
 - **Ultrafast Connectivity**
 - 2.5G LAN
 - **EZ Update**
 - BIOS Flashback Button
 - ASRock Auto Driver Installer
 - **EZ Troubleshooter**
 - [ASRock Post Status Checker](#)
 - CPU
 - Supports AMD Socket AM5 Ryzen™ 9000, 8000 and 7000 Series Processors*
- * The availability of expansion slots may vary by CPU. Please refer to PCIe/M.2 Bandwidth Table for details.
- Chipset
 - AMD B850

- Memory
 - Dual Channel DDR5 Memory Technology
 - 4 x DDR5 DIMM Slots
 - Supports DDR5 ECC/non-ECC, un-buffered memory up to 8000+(OC)
 - Max. capacity of system memory: 256GB
 - Supports Extreme Memory Profile (XMP) and EXTENDED Profiles for Overclocking (EXPO) memory modules
- BIOS
 - 256Mb AMI UEFI Legal BIOS with GUI support
- Graphics
 - Integrated AMD RDNA™ graphics (Actual support may vary by CPU)
 - 1 x HDMI 2.1 TMDS/FRL 8G Compatible, supports HDR, HDCP 2.3 and max. resolution up to 4K 120Hz
 - 1 x USB 3.2 Gen1 Type-C, supports DP 1.4 HBR3 and max. resolution up to 4K 60Hz (DP-alt mode supports DP1.4a)
- Audio
 - 7.1 CH HD Audio (Realtek ALC897 Audio Codec)
- LAN
 - 2.5 Gigabit LAN 10/100/1000/2500 Mb/s
 - Dragon RTL8125BG
 - Supports Dragon 2.5G LAN Software
 - Smart Auto Adjust Bandwidth Control
 - Visual User Friendly UI
 - Visual Network Usage Statistics
 - Optimized Default Setting for Game, Browser, and Streaming Modes
 - User Customized Priority Control
- Slots
 - CPU:
 - 1 x PCIe 5.0 x16 Slot (PCIE1), supports x16 mode*
 - Chipset:
 - 1 x PCIe 4.0 x16 Slot (PCIE2), supports x4 mode*
 - 1 x M.2 Socket (Key E), supports type 2230 WiFi/BT PCIe WiFi module
 - 15µ Gold Contact in VGA PCIe Slot (PCIE1)

* PCIE1 will run at Gen5x16 with 9000 and 7000 series processors, Gen4x8 with 8000 (Phoenix 1) series processors and Gen4x4 with 8000 (Phoenix 2) series processors.

If M2_3 is occupied, PCIE2 will be disabled.
Supports NVMe SSD as boot disks

- Storage
 - CPU:
 - 1 x Blazing M.2 Socket (M2_1, Key M), supports type 2280 PCIe Gen5x4 (128 Gb/s) mode*
 - 1 x Hyper M.2 Socket (M2_2, Key M), supports type 2280 PCIe Gen4x4 (64 Gb/s) mode*
 - Chipset:
 - 1 x Hyper M.2 Socket (M2_3, Key M), supports type 2230/2242/2260/2280 PCIe Gen4x4 (64 Gb/s) mode*
 - 1 x Ultra M.2 Socket (M2_4, Key M), supports type 2280 PCIe Gen3x4 (32 Gb/s) mode*
 - 2 x SATA3 6.0 Gb/s Connectors
 - ASMedia ASM1061:
 - 2 x SATA3 6.0 Gb/s Connectors

* Supports NVMe SSD as boot disks

M2_1 is the first priority for M.2 installation.

M2_1 will run at Gen5x4 with 9000 and 7000 series processors and Gen4x4 with 8000 (Phoenix 1 and Phoenix 2) series processors.

M2_2 will run at Gen4x4 with 9000 and 7000 series processors, Gen4x4 with 8000 (Phoenix 1) series processors and Gen4x2 with 8000 (Phoenix 2) series processors.

If M2_3 is occupied, PCIE2 will be disabled.

If SATA3_1 or SATA3_2 is occupied, M2_4 will

- downgrade to Gen3x2 mode.
- RAID
 - Supports RAID 0 and RAID 1 for SATA storage devices
 - Supports RAID 0, RAID 1 and RAID 10 for M.2 NVMe storage devices
- USB
 - CPU:
 - 1 x USB 3.2 Gen2 Type-C (Rear)
 - 1 x USB 3.2 Gen1 Type-C (Rear)
 - 2 x USB 3.2 Gen1 Type-A (Rear (USB32_1 and USB32_2))
 - Chipset:
 - 1 x USB 3.2 Gen2x2 Type-C (Front)
 - 4 x USB 3.2 Gen1 Type-A (2 Rear (USB32_3 and USB32_4), 2 Front)
 - 9 x USB 2.0 (6 Rear, 3 Front)

* All USB ports support ESD Protection

- Connector
 - 1 x SPI TPM Header
 - 1 x Power LED and Speaker Header
 - 1 x RGB LED Header*
 - 3 x Addressable LED Headers**
 - 2 x CPU Fan Connectors (4-pin) (Smart Fan Speed Control)***
 - 4 x Chassis Fan Connectors (4-pin) (Smart Fan Speed Control)***
 - 1 x AIO Pump Fan Connector (4-pin) (Smart Fan Speed Control)***
 - 1 x 24 pin ATX Power Connector
 - 2 x 8 pin 12V Power Connectors (Hi-Density Power Connector)
 - 1 x Front Panel Audio Connector
 - 2 x USB 2.0 Headers (Support 3 USB 2.0 ports)
 - 1 x USB 3.2 Gen1 Header (Supports 2 USB 3.2 Gen1 ports)
 - 1 x Front Panel Type C USB 3.2 Gen2x2 Header (20 Gb/s)

* Supports in total up to 12V/3A, 36W LED Strip

** Support in total up to 5V/3A, 15W LED Strip

*** CPU_FAN1 supports the fan power up to 1A (12W).

CPU_FAN2, CHA_FAN1~4 and AIO_PUMP support the fan power up to 3A (36W).

CPU_FAN2, CHA_FAN1~4 and AIO_PUMP can auto detect if 3-pin or 4-pin fan is in use.

- Rear Panel I/O
 - 2 x Antenna Mounting Points
 - 1 x HDMI Port
 - 1 x USB 3.2 Gen2 Type-C Port (10 Gb/s)
 - 1 x USB 3.2 Gen1 Type-C Port (DP-alt mode supports DP1.4a)
 - 4 x USB 3.2 Gen1 Type-A Ports
 - 6 x USB 2.0 Ports
 - 1 x RJ-45 LAN Port
 - 1 x BIOS Flashback Button
 - HD Audio Jacks: Line in / Front Speaker / Microphone
- Software and UEFI
 - Software**
 - ASRock Motherboard Utility (A-Tuning)
 - ASRock Dragon 2.5G LAN Software
 - ASRock Polychrome SYNC*
 - UEFI**
 - ASRock EZ Mode
 - ASRock Full HD UEFI
 - ASRock Auto Driver Installer
 - ASRock Instant Flash

*These utilities can be downloaded from ASRock Live Update & APP Shop.

- Accessories
 - 1 x I/O Shield

- 2 x SATA Data Cables
- 1 x Screw for M.2 Socket
- Form Factor
 - ATX Form Factor: 12.0-in x 9.6-in, 30.5 cm x 24.4 cm
 - 8 Layer PCB
- OS
 - Microsoft Windows® 10 64-bit / 11 64-bit