

MATIČNA PLOČA GIGABYTE AM5 X870E AORUS MASTER

Naziv: MATIČNA PLOČA GIGABYTE AM5 X870E AORUS MASTER

Slika:



Šifra: #BM811801731345595100

Barkod: 4719331864354

Proizvođač: GIGABYTE

Detalji

Kategorija: MATIČNE PLOČE

Oznake: **NEMA NA STANJU**

Atributi:

CenaCena sa PDV: 76,990.00 RSD *WEB CENA
84,689.00 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

Model	Gigabyte X870E AORUS MASTER AM5 DDR5 ATX Matična ploča
Procesorsko podnožje (Socket)	AMD Socket AM5
Skup čipova (Chipset)	AMD X870E
Podrška za procesore	AMD Ryzen 9000 Series Processors AMD Ryzen 8000 Series Processors AMD Ryzen 7000 Series Processors
Tip memorije (RAM)	DDR5
Broj memorijskih slotova	4x 288-Pin DDR5
	Support for DDR5 8600(OC) / 8400(OC) / 8200(OC) / 8000(OC) / 7800(OC) / 7600(OC) / 7200(OC) / 7000(OC) / 6800(OC) / 6666(OC) / 6600(OC) / 6400(OC) / 6200(OC) / 6000(OC) / 5600(OC) / 5200 / 4800 /

Podrška za memorije	<p>4400 MT/s memory modules 4 x DDR5 DIMM sockets supporting up to 256 GB (64 GB single DIMM capacity) of system memory Dual channel memory architecture Support for ECC and non-ECC Unbuffered DIMM memory modules Support for AMD EXTended Profiles for Overclocking (AMD EXPO) and Extreme Memory Profile (XMP) memory modules</p>
Podrška za grafiku - portovi	<p>Integrated Graphics Processor with AMD Radeon Graphics support+ASMedia USB4 Controller: - 2 x USB4 USB Type-C ports, supporting USB4 and DisplayPort video outputs and a maximum resolution of 3840x2160 240Hz Support for DisplayPort 1.4 version and HDR.</p> <p>Integrated Graphics Processor with AMD Radeon Graphics support: - 1 x HDMI port, supporting a maximum resolution of 4096x2160 60Hz Support for HDMI 2.1 version, HDCP 2.3, and HDR. Support for native HDMI 2.1 TMDS compatible ports.</p> <p>- 1 x Front HDMI port, supporting a maximum resolution of 1920x1080 30Hz Support for HDMI 1.4 version</p>
Slotovi za proširenja	<p>1 x PCI Express x16 slot (PCIEX16), integrated in the CPU: AMD Ryzen 9000/7000 Series Processors support PCIe 5.0 x16 mode The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot. The PCIEX16 slot shares bandwidth with the M2B_CPU and M2C_CPU connectors. The PCIEX16 slot operates at up to x8 mode when a device is installed in the M2B_CPU or M2C_CPU connector.</p> <p>AMD Ryzen 8000 Series-Phoenix 1 Processors support PCIe 4.0 x8 mode AMD Ryzen 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4 mode</p> <p>Chipset: - 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x4 (PCIEX4_1) - 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x4 (PCIEX4_2)</p>
M.2 portovi	4x M.2 Socket 3
	<p>1 x M.2 connector (M2A_CPU), integrated in the CPU, supporting Socket 3, M key, type 25110/22110/2580/2280 SSDs: AMD Ryzen 9000/7000 Series Processors support PCIe 5.0 x4/x2 SSDs</p>

Čuvanje podataka - portovi

AMD Ryzen 8000 Series-Phoenix 1 Processors support PCIe 4.0 x4/x2 SSDs

AMD Ryzen 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4/x2 SSDs

2 x M.2 connectors (M2B_CPU, M2C_CPU), integrated in the CPU, supporting Socket 3, M key, type 22110/2280 SSDs:

AMD Ryzen 9000/7000 Series Processors support PCIe 5.0 x4/x2 SSDs

The M2B_CPU and M2C_CPU connectors become unavailable when an AMD Ryzen 8000 Series-Phoenix 1/Phoenix 2 processor is used.

1 x M.2 connector (M2D_SB), integrated in the Chipset, supporting Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSDs

4 x SATA 6Gb/s connectors
RAID 0, RAID 1, RAID 5, and RAID 10 support for NVMe SSD storage devices
RAID 5 is only available on AMD Ryzen 9000 Series Processors.

RAID 0, RAID 1, and RAID 10 support for SATA storage devices

SATA portovi

4x SATA 6Gb/s

LAN

Realtek 5GbE LAN chip (5 Gbps/2.5 Gbps/1 Gbps/100 Mbps)

Bežična mreža

Qualcomm Wi-Fi 7 QCNCM865 - 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency bands
- Support for 11be 320MHz wireless standard

Bluetooth

5.3

Zvuk (Audio)

Realtek ALC1220 CODEC
The back panel line out jack supports DSD audio.

Support for DTS:X Ultra High Definition Audio
2/4/5.1/7.1-channel
Support for S/PDIF Out

USB portovi

CPU+ASMedia USB4 controller:
- 2 x USB4 USB Type-C ports on the back panel
CPU:
- 1 x USB 3.2 Gen 2 Type-A port (red) on the back panel
Chipset+USB 3.2 Gen 1 Hub:
- 4 x USB 3.2 Gen 1 ports on the back panel
Chipset:
- 1 x USB Type-C port with USB 3.2 Gen 2x2 support, available through the internal USB header
- 3 x USB 3.2 Gen 2 Type-A ports (red) on the back panel
- 4 x USB 3.2 Gen 1 ports available through the internal USB headers
- 6 x USB 2.0/1.1 ports (2 ports on the

	back panel, 4 ports available through the internal USB headers)
Konektori na zadnjoj strani	<ul style="list-style-type: none"> 1 x Q-Flash Plus button 1 x Clear CMOS button 1 x HDMI port (Note) 2 x USB4 USB Type-C ports (DisplayPorts (Note)) 4 x USB 3.2 Gen 2 Type-A ports (red) 4 x USB 3.2 Gen 1 ports 2 x USB 2.0/1.1 ports 1 x RJ-45 port 2 x antenna connectors (2T2R) 2 x audio jacks 1 x optical S/PDIF Out connector (Note) Actual support may vary by CPU.
Unutrašnji konektori	<ul style="list-style-type: none"> 1 x 24-pin ATX main power connector 2 x 8-pin ATX 12V power connectors 1 x CPU fan header 1 x CPU fan/water cooling pump header 4 x system fan headers 2 x system fan/water cooling pump headers 4 x addressable RGB Gen2 LED strip headers 1 x RGB LED strip header 4 x M.2 Socket 3 connectors 4 x SATA 6Gb/s connectors 1 x front panel header 1 x front panel audio header 1 x USB Type-C header, with USB 3.2 Gen 2x2 support 2 x USB 3.2 Gen 1 headers 2 x USB 2.0/1.1 headers 1 x noise detection header 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only) 1 x HDMI port (Note) 1 x power button 1 x reset button 1 x reset jumper 1 x Clear CMOS jumper 2 x temperature sensor headers Voltage Measurement Points
Posebne mogućnosti	<ul style="list-style-type: none"> Support for Q-Flash Support for Q-Flash Plus Support for Smart Backup Voltage detection Temperature detection Fan speed detection Water cooling flow rate detection Fan fail warning Fan speed control Whether the fan (pump) speed control function is supported will depend on the fan (pump) you install. Noise detection
Operativni sistem	Windows 11
BIOS	<ul style="list-style-type: none"> 1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Format	ATX

Prava
potrošača:

Zakonska saobraznost 2 godine

EAN:

4719331864354