


SERVER DELL POWEREDGE T150 XEON E-2314 4C 16GB 1X2TB PERC H355Naziv: SERVER DELL POWEREDGE T150 XEON E-2314 4C
16GB 1X2TB PERC H355

Šifra: #BM512111732377706430

Barkod: 5902002167659

Proizvođač: DELL

Detalji

Kategorija: SERVERI

Oznake: NOVO

NEMA NA STANJU

Atributi:

CenaCena sa PDV: 183,748.00 RSD *WEB CENA
202,122.80 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:	Basic data	
	Item name	PowerEdge T150, Chassis 4 x 3.5", Xeon E-2314, 16GB, 1x2TB, Broadcom 5720 Dual Port, PERC H355 Adapter, Full Height, iDRAC9 Basic 15G
	Product symbol	PET150CM2
	Hierarchy by CATEGORY	<ul style="list-style-type: none">Computers & PeripheralsComputersServers
	Hierarchy by MANUFACTURER	<ul style="list-style-type: none">Dell
	Package sizes (HxWxL)	380 x 500 x 390 mm
	Weight gross	12 kg

Weight & dimensions	
Height	<ul style="list-style-type: none"> 360.00 millimeter
Width	<ul style="list-style-type: none"> 175.00 millimeter
Depth	<ul style="list-style-type: none"> 453.75 millimeter
Weight	<ul style="list-style-type: none"> 11680.00 gram
Power	
Power cable length	<ul style="list-style-type: none"> 2.00 meter
Power cable current	<ul style="list-style-type: none"> 10.00 A
Power cable connector 1	<ul style="list-style-type: none"> C13 coupler
Power cable connector 2	<ul style="list-style-type: none"> C14 coupler
Carbon footprint	
Total carbon footprint (kg of CO2e)	<ul style="list-style-type: none"> 2230
icecat_automatic_47440_305	<ul style="list-style-type: none"> 1010
icecat_automatic_47441_305	<ul style="list-style-type: none"> 457
Carbon emissions, logistics (kg of CO2e)	<ul style="list-style-type: none"> 139
Carbon emissions, energy usage (kg of CO2e)	<ul style="list-style-type: none"> 1610
icecat_automatic_47444_305	<ul style="list-style-type: none"> 21
icecat_automatic_47445_305	<ul style="list-style-type: none"> 617
icecat_automatic_47446_305	<ul style="list-style-type: none"> 1.3.2, 2022
Software	
Compatible operating systems	<ul style="list-style-type: none"> Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server

	Citrix Hypervisor Canonical Ubuntu Server LTS
Operating system installed	<ul style="list-style-type: none"> No
Design	
Chassis type	<ul style="list-style-type: none"> Rack (4U)
Product color	<ul style="list-style-type: none"> Black
Storage	
HDD size	<ul style="list-style-type: none"> 3.5
Optical drive type	<ul style="list-style-type: none"> No
Total storage capacity	<ul style="list-style-type: none"> 2000.00 GB
Supported RAID controllers	<ul style="list-style-type: none"> PERC H355
HDD speed	<ul style="list-style-type: none"> 7200
HDD capacity	<ul style="list-style-type: none"> 2000.00 GB
Supported HDD sizes	<ul style="list-style-type: none"> 3.5
HDD interface	<ul style="list-style-type: none"> SATA
Network	
Ethernet interface type	<ul style="list-style-type: none"> Gigabit Ethernet
Cabling technology	<ul style="list-style-type: none"> 10/100/1000Base-T(X)
Memory	
Internal memory type	<ul style="list-style-type: none"> DDR4-SDRAM
Memory clock speed	<ul style="list-style-type: none"> 3200.00 MHz
Maximum internal memory	<ul style="list-style-type: none"> 64.00 GB
Buffered memory type	<ul style="list-style-type: none"> Unregistered (unbuffered)

Internal memory	<ul style="list-style-type: none">• 16.00 GB
Memory slots	<ul style="list-style-type: none">• 4x DIMM
Memory layout (slots x size)	<ul style="list-style-type: none">• 1 x 16 GB
Processor	
Processor frequency	<ul style="list-style-type: none">• 2.80 GHz
Processor cache	<ul style="list-style-type: none">• 8.00 MB
Processor manufacturer	<ul style="list-style-type: none">• Intel
Processor family	<ul style="list-style-type: none">• Intel Xeon E
Processor boost frequency	<ul style="list-style-type: none">• 4.50 GHz
Processor model	<ul style="list-style-type: none">• E-2314
Performance	
Remote administration	<ul style="list-style-type: none">• iDRAC9 Basic 15G