

LAN ROUTER TP-LINK TL-MR100 3G/4G LTE WIFI 5 DUALBAND 1XLAN/1XWAN 150MB/S

Naziv: LAN ROUTER TP-LINK TL-MR100 3G/4G LTE WIFI 5 DUALBAND 1XLAN/1XWAN 150MB/S

Slika:



Šifra: #BM4366901732377706824

Barkod: 6935364088804

Proizvođač: TP-LINK

Detalji

Kategorija: RUTERI

Oznake:

Atributi:

CenaCena sa PDV: 9,829.00 RSD *WEB CENA
10,811.90 RSD *Cena za odloženo web plaćanje**Ostalo**

Opis:

HARDWARE FEATURES

Interface	1 10/100Mbps LAN Port, 1 10/100Mbps LAN/WAN Port, 1 Micro SIM Card Slot
Button	WPS/Reset Button
External Power Supply(EU)	9V/0.85A
Dimensions (W x D x H)	6.06×4.49×1.42 in (154×114×36 mm)
Antenna	2 Detachable External 4G LTE Antennas
Antenna Type	V3/APAC: 2 Internal 4G LTE Antennas V4/V2/V1: 2 Detachable 4G LTE Antennas

WIRELESS FEATURES

Wireless Standards	IEEE 802.11b/g/n
Frequency	2.4 GHz

Signal Rate	300 Mbps
Reception Sensitivity	11g 54M: -74 dBm 11n HT20: -71 dBm 11n HT40: -68 dBm
Transmit Power	< 20 dBm (2.4 GHz)
Wireless Functions	Enable/Disable Wireless Radio, Wireless Schedule, WMM, Wireless Statistics
WAN Failover	Yes
Wireless Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions
Network Type	4G: FDD-LTE: B1/B3/B5/B7/B8/B20 (2100/1800/850/2600/900/800 MHz) TDD-LTE: B38/B40/B41 (2600/2300/2500 MHz) 3G: HSPA/UMTS: B1/B5/B8 (2100/850/900 MHz)

SOFTWARE FEATURES

Security	IPv4 SPI Firewall, IP and MAC Address Binding
Operating Modes	3G/4G Router, Wireless Router
WAN Type	Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)
Management	Local Management, Remote Management
DHCP	Server, DHCP Client List, Address Reservation
Port Forwarding	ALG, Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS	DynDns, NO-IP
Protocols	IPv4, IPv6
Guest Network	2.4 GHz Guest Network
Administration	Upgrade Firmware, Factory Default, System Log, Diagnostic Tools

OTHERS

Certification	CE, RoHS
Package Contents	300 Mbps Wireless N 4G LTE TL-MR100 Power Adapter RJ45 Ethernet Cable Quick Installation Guide
Requirements	Microsoft Windows 98SE/NT/2000/XP/Vista™/7/8/8.1/10, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser Micro SIM Card

Environment

Operating Temperature: 0°C~40°C
(32°F ~104°F)
Storage Temperature: -40°C~70°C
(-40°F ~158°F)
Operating Humidity: 10%~90% non-
condensing
Storage Humidity: 5%~90% non-
condensing

Link [LAN Router TP-LINK TL-MR100 3G/4G LTE WiFi
1xLAN/1xWAN 150mb/s](#)