

**SERVER DELL POWEREDGE R250 XEON E-2314 4C 1X16GB 1X480GB PERC H355 450W 3YR**Naziv: SERVER DELL POWEREDGE R250 XEON E-2314 4C  
1X16GB 1X480GB PERC H355 450W 3YR

Slika:



Šifra: #BM512111732378006165

Barkod: 5902002250115

Proizvođač: DELL

**Detalji**

Kategorija: SERVERI

Oznake: NOVO

Atributi:

**Cena**Cena sa PDV: 256,411.00 RSD \*WEB CENA  
282,052.10 RSD \*Cena za odloženo web plaćanje**Ostalo**

Opis:

Basic data	
Item name	DELL PowerEdge R250 server 480 GB Rack (1U) Intel Xeon E E-2314 2.8 GHz 16 GB DDR4-SDRAM 450 W
Product symbol	emea_per250spl4
Hierarchy by CATEGORY	<ul style="list-style-type: none"><li>Computers &amp; Peripherals</li><li>Computers</li><li>Servers</li></ul>
Hierarchy by MANUFACTURER	<ul style="list-style-type: none"><li>Dell</li></ul>
Package sizes (HxWxL)	250 x 600 x 920 mm
Weight gross	23 kg
Other features	
Data transfer rate	<ul style="list-style-type: none"><li>6.00 Gb/s</li></ul>

Bytes per sector	<ul style="list-style-type: none"> <li>• 512</li> </ul>
Weight & dimensions	
Width	<ul style="list-style-type: none"> <li>• 482.00 millimeter</li> </ul>
Height	<ul style="list-style-type: none"> <li>• 42.80 millimeter</li> </ul>
Weight	<ul style="list-style-type: none"> <li>• 12480.00 gram</li> </ul>
Power	
Power cable length	<ul style="list-style-type: none"> <li>• 2.00 meter</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• 450.00 W</li> </ul>
Power cable current	<ul style="list-style-type: none"> <li>• 10.00 A</li> </ul>
Power cable connector 1	<ul style="list-style-type: none"> <li>• C13 coupler</li> </ul>
Power cable connector 2	<ul style="list-style-type: none"> <li>• C14 coupler</li> </ul>
Carbon footprint	
Total carbon footprint (kg of CO2e)	<ul style="list-style-type: none"> <li>• 2100</li> </ul>
icecat_automatic_47440_305	<ul style="list-style-type: none"> <li>• 935</li> </ul>
icecat_automatic_47441_305	<ul style="list-style-type: none"> <li>• 505</li> </ul>
Carbon emissions, logistics (kg of CO2e)	<ul style="list-style-type: none"> <li>• 110</li> </ul>
Carbon emissions, energy usage (kg of CO2e)	<ul style="list-style-type: none"> <li>• 1470</li> </ul>
icecat_automatic_47444_305	<ul style="list-style-type: none"> <li>• 17</li> </ul>
icecat_automatic_47445_305	<ul style="list-style-type: none"> <li>• 632</li> </ul>
icecat_automatic_47446_305	<ul style="list-style-type: none"> <li>• 1.3.2, 2022</li> </ul>
Software	
	<ul style="list-style-type: none"> <li>• Canonical® Ubuntu® Server LTS Citrix®</li> </ul>

Compatible operating systems	Hypervisor Microsoft® Windows Server® with Hyper-V RedHat® Enterprise Linux SUSE® Linux Enterprise Server VMware® ESXi®
Operating system installed	<ul style="list-style-type: none"> <li>No</li> </ul>
Design	
Chassis type	<ul style="list-style-type: none"> <li>Rack (1U)</li> </ul>
Product color	<ul style="list-style-type: none"> <li>Black</li> </ul>
Storage	
Supported RAID controllers	<ul style="list-style-type: none"> <li>PERC H355</li> </ul>
Optical drive type	<ul style="list-style-type: none"> <li>No</li> </ul>
Total storage capacity	<ul style="list-style-type: none"> <li>480.00 GB</li> </ul>
SSD size	<ul style="list-style-type: none"> <li>2.5"</li> </ul>
SSD interface	<ul style="list-style-type: none"> <li>SATA III</li> </ul>
SSD capacity	<ul style="list-style-type: none"> <li>480.00 GB</li> </ul>
Supported SSD sizes	<ul style="list-style-type: none"> <li>3.5"</li> </ul>
Network	
Ethernet interface type	<ul style="list-style-type: none"> <li>Gigabit Ethernet</li> </ul>
Cabling technology	<ul style="list-style-type: none"> <li>10/100/1000Base-T(X)</li> </ul>
LAN controller	<ul style="list-style-type: none"> <li>Broadcom 5720</li> </ul>
Memory	
Memory clock speed	<ul style="list-style-type: none"> <li>3200.00 MHz</li> </ul>
Internal memory	<ul style="list-style-type: none"> <li>16.00 GB</li> </ul>
Maximum internal memory	<ul style="list-style-type: none"> <li>128.00 GB</li> </ul>

Internal memory type	<ul style="list-style-type: none"><li>• DDR4-SDRAM</li></ul>
Memory slots	<ul style="list-style-type: none"><li>• 4x DIMM</li></ul>
Memory layout (slots x size)	<ul style="list-style-type: none"><li>• 1 x 16 GB</li></ul>
Processor	
Processor frequency	<ul style="list-style-type: none"><li>• 2.80 GHz</li></ul>
Processor cache	<ul style="list-style-type: none"><li>• 8.00 MB</li></ul>
Processor manufacturer	<ul style="list-style-type: none"><li>• Intel</li></ul>
Processor family	<ul style="list-style-type: none"><li>• Intel Xeon E</li></ul>
Processor boost frequency	<ul style="list-style-type: none"><li>• 4.50 GHz</li></ul>
Processor model	<ul style="list-style-type: none"><li>• E-2314</li></ul>
Performance	
Remote administration	<ul style="list-style-type: none"><li>• iDRAC9 Express 15G</li></ul>