

MB AM4 ASUS PRIME B550M-K

Naziv: MB AM4 ASUS PRIME B550M-K
Slika:



Šifra: #BM7611801726044151460
Barkod: 4718017758284
Proizvođač: ASUS

Detalji

Kategorija: MATIČNE PLOČE
Oznake:
Atributi:

Cena

Cena sa PDV: 11,990.00 RSD *WEB CENA
13,189.00 RSD *Cena za odloženo web plaćanje

Ostalo

Opis:

Podnožje	AMD® AM4
Čipset	AMD® B550
Tip procesora	AMD
Format ploče	Micro ATX
Podržani procesori	- Ugrađeni AMD AM4 podnožje za 3rd Gen AMD Ryzen i 3rd Gen AMD Ryzen sa Radeon grafičkim procesorima
Podržana memorija	DDR4
Memorija	- 3rd Gen AMD Ryzen Procesora - 4 x DIMM, Max. 128GB, DDR4 4600(O.C.)/4400(O.C.)/4266(O.C.)/4133(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.)/3600(O.C.)/3466(O.C.)/3333(O.C.)/3200/3000/2800/2666/2400/2133 MHz Un-buffered memoriju - 3rd Gen AMD Ryzen sa Radeon grafičkim procesorima - 4 x DIMM, Max. 128GB, DDR4 4800(O.C.)/4600(O.C.)/4466(O.C.)/4400(O.C.)/4266(O.C.)/4133(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.)/3600(O.C.)/3466(O.C.)/3333(O.C.)/3200/3000/2800/2666/2400/2133 MHz Un-buffered memoriju - Dual Channel Memory Architecture - ECC Memory (ECC mode) podrška varira od CPU
Integrirana grafička karta	- 1 x D-Sub - 1 x DVI-D - 1 x HDMI 2.1(4K@60HZ)
Slotovi za proširenje	- 3rd Gen AMD Ryzen procesori - 1 x PCIe 4.0 x16 (x16 mode) - 3rd Gen AMD Ryzen sa Radeon grafičkim procesorima - 1 x PCIe 3.0 x16 (x16 mode) - AMD B550 Chipset - 2 x PCIe 3.0 x1
Skladište	Maksimalno podržava 2 x M.2 slot(s) i 4 x SATA 6Gb/s porta - 3rd Gen AMD Ryzen procesori: - 1 x M.2_1 podnožje 3, sa M Key, tip 2242/2260/2280/22110(PCIE 4.0 x4 i SATA modes) storage uređaja - 3rd Gen AMD Ryzen sa Radeon grafičkim procesorima: - 1 x M.2_1 podnožje 3, sa M Key, tip 2242/2260/2280/22110(PCIE 3.0 x4 i SATA modes) storage uređaja - AMD B550 Chipset : - 1 x M.2_2 podnožje 3, sa M Key, tip 2242/2260/2280 (PCIE 3.0 x4 i SATA modes) storage uređaja - 4 x SATA 6Gb/s port(s) - Podržava Raid 0, 1, 10
Mrežna karta	- Realtek RTL8111H 1Gb Ethernet - ASUS LANGuard
Zvučna karta	Realtek ALC887 7.1 Surround Sound High Definition Audio CODEC - Podržava: Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit/192kHz playback Audio Feature : - LED-illuminated design - Audio Shielding - Dedicated audio PCB layers - Premium Japanese audio capacitors
USB	USB portovi sa zadnje strane (Total 6) - 2 x USB 3.2 Gen 2 port(s)(2 x Type-A) - 4 x USB 3.2 Gen 1 port(s)(4 x Type-A) USB portovi sa prednje strane (Total 6) - 2 x USB 3.2 Gen 1 port(s)(2 x Type-A) - 4 x USB 2.0 port(s)(4 x Type-A)
Konektori na zadnjoj strani	- 1 x PS/2 keyboard/mouse combo port(s) - 1 x DVI-D - 1 x D-Sub - 1 x HDMI - 1 x LAN (RJ45) port(s) - 2 x USB 3.2 Gen 2 (teal blue) (2 x Type-A) - 4 x USB 3.2 Gen 1 (blue) Type-A - 3 x Audio jack(s)
Interni konektori	- 1 x CPU Fan connector(s) - 2 x Chassis Fan connector(s) - 1 x USB 3.2 Gen 1(up to 5Gbps) konektor podržava dodatna 2 USB 3.2 Gen 1 port(s) - 2 x USB 2.0 konektora podržavaju dodatna 4 USB 2.0 port(s) - 1 x M.2 podnožje 3 sa M Key, tip 2242/2260/2280/22110 storage uedajja (SATA mode & X4 PCIE mode) - 1 x M.2 podnožje 3 sa M Key, tip 2242/2260/2280 storage uređaja (SATA mode & X4 PCIE mode) - 1 x SPI TPM header - 4 x SATA 6Gb/s connector(s) - 1 x S/PDIF out header(s) - 1 x 24-pin EATX Power connector(s) - 1 x 8-pin EATX 12V Power connectors - 1 x Front panel audio connector(s) (AAFP) - 1 x Clear CMOS jumper(s) - 1 x System panel connector - 1 x COM port header - 1 x Speaker connector
BIOS	- 256 Mb Flash ROM, UEFI AMI BIOS