

MB AM5 ASROCK B650 PRO RS 90-MXBL10-A0UAYZ

Naziv: MB AM5 ASROCK B650 PRO RS 90-MXBL10-A0UAYZ

Slika:



Šifra: #BM42511801726044156336

Barkod: 4710483940750

Proizvođač: ASROCK

Detalji

Kategorija: MATIČNE PLOČE

Oznake: **NEMA NA STANJU**

Atributi:

CenaCena sa PDV: 27,378.00 RSD *WEB CENA
30,115.80 RSD *Cena za odloženo web plaćanje**Ostalo**

- Opis:
- CPU
 - Supports AMD Socket AM5 Ryzen™ 7000 Series Processors
 - Chipset
 - AMD B650
 - Memory
 - Dual Channel DDR5 Memory Technology
 - 4 x DDR5 DIMM Slots
 - Supports DDR5 non-ECC, un-buffered memory up to 6400+(OC)
 - Max. capacity of system memory: 192GB
 - Supports Extreme Memory Profile (XMP) and EXTENDED Profiles for Overclocking (EXPO) memory modules
 - BIOS
 - 256Mb AMI UEFI Legal BIOS with GUI support
 - Graphics
 - Integrated AMD RDNA™ 2 graphics (Actual support may vary by CPU)
 - 1 x HDMI 2.1 TMDS/FRL 8G Compatible, supports HDR, HDCP 2.3 and max. resolution up to 4K 120Hz
 - 1 x DisplayPort 1.4 with DSC (compressed), supports HDCP 2.3 and max. resolution up to 4K 120Hz
 - Audio
 - 7.1 CH HD Audio (Realtek ALC897 Audio)

Codec)

- Nahimic Audio

- o LAN

- 2.5 Gigabit LAN 10/100/1000/2500 Mb/s

- Dragon RTL8125BG

- Supports Dragon 2.5G LAN Software

- Smart Auto Adjust Bandwidth Control

- Visual User Friendly UI

- Visual Network Usage Statistics

- Optimized Default Setting for Game, Browser, and Streaming Modes

- User Customized Priority Control

- Slots

CPU:

- 1 x PCIe 4.0 x16 Slot (PCIe1), supports x16 mode*

- 1 x PCIe 3.0 x16 Slot (PCIe3), supports x4 mode*

Chipset:

- 1 x PCIe 4.0 x1 Slot (PCIe2)*

- 1 x M.2 Socket (Key E), supports type 2230 WiFi/BT PCIe WiFi module*

- Supports AMD CrossFire™

- 15µ Gold Contact in VGA PCIe Slot (PCIe1)

*Supports NVMe SSD as boot disks

- Storage

CPU:

- 1 x Blazing M.2 Socket (M2_1, Key M), supports type 2280 PCIe Gen5x4 (128 Gb/s) mode*

Chipset:

- 1 x M.2 Socket (M2_2, Key M), supports type 2242/2260/2280 SATA3 6.0 Gb/s & PCIe Gen3x2 (16 Gb/s) modes*

- 1 x Hyper M.2 Socket (M2_3, Key M), supports type 2260/2280 PCIe Gen4x4 (64 Gb/s) mode*

- 2 x SATA3 6.0 Gb/s Connectors

ASMedia ASM1061:

- 2 x SATA3 6.0 Gb/s Connectors

*Supports NVMe SSD as boot disks

Supports ASRock U.2 Kit

- RAID

- Supports RAID 0 and RAID 1 for SATA storage devices

- Supports RAID 0, RAID 1 and RAID 10 for M.2 NVMe storage devices*

*Requires additional M.2 NVMe expansion cards to support RAID 10

- USB

- 1 x USB 3.2 Gen2x2 Type-C (Front)

- 1 x USB 3.2 Gen2 Type-C (Rear)

- 1 x USB 3.2 Gen2 Type-A (Rear)

- 4 x USB 3.2 Gen1 (2 Rear, 2 Front)

- 9 x USB 2.0 (6 Rear, 3 Front)

*All USB ports support ESD Protection

- Connector

- 1 x SPI TPM Header

- 1 x Power LED and Speaker Header

- 1 x RGB LED Header*

- 3 x Addressable LED Headers**

- 1 x CPU Fan Connector (4-pin)***

- 1 x CPU/Water Pump Fan Connector (4-pin) (Smart Fan Speed Control)****

- 4 x Chassis/Water Pump Fan Connectors (4-pin) (Smart Fan Speed Control)*****

- 1 x 24 pin ATX Power Connector

- 1 x 8 pin 12V Power Connector

- 1 x 4 pin 12V Power Connector

- 1 x Front Panel Audio Connector

- 1 x Thunderbolt™ AIC Connector (5-pin)
(Supports ASRock Thunderbolt™ 4 AIC Card)
- 2 x USB 2.0 Headers (Support 3 USB 2.0 ports)
- 1 x USB 3.2 Gen1 Header (Supports 2 USB 3.2 Gen1 ports)
- 1 x Front Panel Type C USB 3.2 Gen2x2 Header (20 Gb/s) (ReDriver)

*Supports in total up to 12V/3A, 36W LED Strip

**Support in total up to 5V/3A, 15W LED Strip

***CPU_FAN1 supports the fan power up to 1A (12W).

**** CPU_FAN2/WP supports the fan power up to 2A (24W).

*****CHA_FAN1~4/WP support the fan power up to 2A (24W).

CPU_FAN2/WP and CHA_FAN1~4/WP can auto detect if 3-pin or 4-pin fan is in use.

- Rear Panel I/O
 - 2 x Antenna Mounting Points
 - 1 x HDMI Port
 - 1 x DisplayPort 1.4
 - 1 x USB 3.2 Gen2 Type-A Port (10 Gb/s) (ReDriver)
 - 1 x USB 3.2 Gen2 Type-C Port (10 Gb/s) (ReDriver)
 - 2 x USB 3.2 Gen1 Ports
 - 6 x USB 2.0 Ports
 - 1 x RJ-45 LAN Port
 - 1 x BIOS Flashback Button
 - HD Audio Jacks: Line in / Front Speaker / Microphone