


MB AM4 ASUS PRIME B550M-A

Naziv:	MB AM4 ASUS PRIME B550M-A
Slika:	
Šifra:	#BM7611801726044203032
Barkod:	4718017755528
Proizvođač:	ASUS

Detalji

Kategorija:	MATIČNE PLOČE
Oznake:	NEMA NA STANJU
Atributi:	

Cena

Cena sa PDV:	14,740.00 RSD *WEB CENA 16,214.00 RSD *Cena za odloženo web plaćanje
--------------	---

Ostalo

Opis:

CPU

AMD AM4 Socket for AMD Ryzen™ 5000 Series/ 5000 G-Series/ 4000 G-Series/ 3000 Series Desktop Processors *
* Refer to www.asus.com for CPU support list

Chipset

AMD B550

Memory

4 x DIMM, Max. 128GB, DDR4
4866(O.C.)/4800(O.C.)/4600(O.C.)/4466(O.C.)/4400(O.C.)/4333(O.C.)/4266(O.C.)/4200(O.C.)/4133(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.)/3600(O.C.)/3466(O.C.)/3400(O.C.)/3333(O.C.)/3200(O.C.) MHz Un-buffered Memory *
Dual Channel Memory Architecture
ECC Memory (ECC mode) support varies by CPU.
* Refer to www.asus.com for the Memory QVL (Qualified Vendors Lists), and memory frequency support depends on the CPU types.

Graphic

1 x D-Sub
1 x DVI-D
1 x HDMI 2.1(4K@60HZ)

*Graphics specifications may vary between CPU types.

Expansion Slots**AMD Ryzen™ 5000 Series/ 3000 Series Desktop Processors**

1 x PCIe 4.0 x16 (x16 mode)

AMD Ryzen™ 5000 G-Series/ 4000 G-Series Desktop Processors

1 x PCIe 3.0 x16 (x16 mode)

AMD B550 Chipset

2 x PCIe 3.0 x1

Storage**Total supports 2 x M.2 slot(s) and 4 x SATA 6Gb/s ports****AMD Ryzen™ 5000 Series/ 3000 Series Desktop Processors :**

1 x M.2_1 socket 3, with M Key, Type 2242/2260/2280/22110(PCIE 4.0 x4 and SATA modes) storage devices support

AMD Ryzen™ 5000 G-Series/ 4000 G-Series Desktop Processors :

1 x M.2_1 socket 3, with M Key, Type 2242/2260/2280/22110(PCIE 3.0 x4 and SATA modes) storage devices support

AMD B550 Chipset :

1 x M.2_2 socket 3, with M Key, Type 2242/2260/2280 (PCIE 3.0 x4 and SATA modes) storage devices support

4 x SATA 6Gb/s port(s),

Support Raid 0, 1, 10

LAN

Realtek RTL8111H 1Gb Ethernet

Audio

Realtek ALC887/897 7.1 Surround Sound High Definition Audio CODEC

- Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit/192kHz playback

Audio Feature :

- LED-illuminated design
 - Audio Shielding
 - Dedicated audio PCB layers
 - Premium Japanese audio capacitors
- * Choose the chassis with HD audio module in front panel to support 8-channel audio output.

USB Ports**Rear USB Port (Total 6)**

2 x USB 3.2 Gen 2 port(s)(2 x Type-A)

4 x USB 3.2 Gen 1 port(s)(4 x Type-A)

Front USB Port (Total 6)

2 x USB 3.2 Gen 1 port(s)(2 x Type-A)
4 x USB 2.0 port(s)(4 x Type-A)

Software Features

ASUS Exclusive Software
Armoury Crate
- Aura Creator
- Aura Sync
AI Suite 3
- Performance And Power Saving Utility
TurboV EVO
EPU
Digi+ VRM
Fan Xpert 2+
- EZ update
ASUS CPU-Z
AI Charger
DAEMON Tools
Norton Anti-virus software (Free Trial for 60 days)
WinRAR
UEFI BIOS
ASUS EZ DIY
- ASUS CrashFree BIOS 3
- ASUS EZ Flash 3
- ASUS UEFI BIOS EZ Mode

ASUS Special Features

ASUS 5X PROTECTION III
- ASUS DIGI+ VRM
- ASUS LANGuard
- ASUS Overvoltage Protection
- ASUS SafeSlot Core
- ASUS Stainless-Steel Back I/O
ASUS Q-Design
- ASUS Q-DIMM
- ASUS Q-Slot
ASUS Thermal Solution
- Aluminum heatsink design
AURA Sync
- Standard RGB headers
- Addressable Gen 2 RGB header
ASUS Lighting Control

Back I/O Ports

1 x PS/2 keyboard/mouse combo port(s)
1 x DVI-D
1 x D-Sub
1 x HDMI
1 x LAN (RJ45) port(s)
2 x USB 3.2 Gen 2 (teal blue) (2 x Type-A)
4 x USB 3.2 Gen 1 (blue) Type-A
3 x Audio jack(s)

Internal I/O Ports

1 x CPU Fan connector(s)
1 x CPU OPT Fan connector(s)
2 x Chassis Fan connector(s)
2 x Aura RGB Strip Headers
1 x Addressable Gen 2 header(s)
1 x USB 3.2 Gen 1(up to 5Gbps) connector(s) support(s) additional 2 USB 3.2 Gen 1 port(s)
2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s)
1 x M.2 Socket 3 with M Key, type 2242/2260/2280/22110 storage devices support (SATA mode & X4 PCIe mode)
1 x M.2 Socket 3 with M Key, type 2242/2260/2280 storage devices support (SATA mode & X4 PCIe mode)
1 x SPI TPM header
4 x SATA 6Gb/s connector(s)
1 x S/PDIF out header(s)
1 x 24-pin EATX Power connector(s)
1 x 8-pin EATX 12V Power connectors
1 x Front panel audio connector(s) (AAFP)
1 x Clear CMOS jumper(s)
1 x System panel connector
1 x COM port header
1 x Speaker connector

Accessories

I/O Shield
2 x SATA 6Gb/s cable(s)
1 x Supporting DVD
User manual
1 x M.2 SSD screw package(s)

BIOS

256 Mb Flash ROM, UEFI AMI BIOS

Manageability

WOL by PXE

Operating System

Windows® 10 64-bit

Form Factor

mATX Form Factor
9.6 inch x 9.6 inch (24.4 cm x 24.4 cm)